

Tube length table for Converters

德国汉森电子变压器负载表


The values given represent the maximum tube lengths which may be connected to the EVG.

每组灯包含一支灯管和一对电极

The tube length is measured from one electrode to the other.

*每对电极消耗约250V之电压

Basis for the calculation of these values are the filling pressure recommendations of the German Fachverband Lichtwerbung as of Nov. 1992.



(混合气) Blue discharge (outdoor) (户外)

Diameter	10	12	15	18	20	22
1 Syst.	0,9	1,1	1,4	1,7	1,8	2,0
2 Syst.	0,5	0,6	0,8	0,9	1,0	1,1

(混合气) Blue discharge (indoor) (户内)

Diameter	10	12	15	18	20	22
1 Syst.	1,2	1,5	1,8	2,1	2,3	2,5
2 Syst.	0,8	1,0	1,2	1,4	1,5	1,6

(NEON 红气) Red discharge

Diameter	10	12	15	18	20	22
1 Syst.	0,6	0,7	0,9	1,1	1,2	1,2
2 Syst.	0,3	0,4	0,5	0,6	0,6	0,7

990 Volt

Blue discharge (outdoor)

Diameter	10	12	15	18	20	22
1 Syst.	1,6	2,0	2,5	2,9	3,1	3,4
2 Syst.	1,2	1,5	1,8	2,1	2,3	2,5
3 Syst.	0,8	1,0	1,2	1,4	1,5	1,7

Blue discharge (indoor)

Diameter	10	12	15	18	20	22
1 Syst.	2,0	2,5	3,0	3,5	3,8	4,1
2 Syst.	1,6	2,0	2,4	2,8	3,0	3,3
3 Syst.	1,2	1,5	1,8	2,1	2,3	2,5

Red discharge

Diameter	10	12	15	18	20	22
1 Syst.	1,0	1,2	1,6	1,9	2,0	2,1
2 Syst.	0,7	0,9	1,2	1,4	1,5	1,6
3 Syst.	0,5	0,6	0,8	0,9	1,0	1,0

1,500 Volt

Blue discharge (outdoor)

Diameter	10	12	15	18	20	22
1 Syst.	2,3	2,8	3,5	4,1	4,4	4,8
2 Syst.	1,9	2,3	2,9	3,4	3,6	4,0
3 Syst.	1,5	1,8	2,2	2,6	2,8	3,1
4 Syst.	1,0	1,3	1,6	1,9	2,1	2,2
5 Syst.	0,6	0,8	1,0	1,2	1,3	1,4

Blue discharge (indoor)

Diameter	10	12	15	18	20	22
1 Syst.	2,8	3,5	4,2	5,0	5,3	5,8
2 Syst.	2,4	3,0	3,6	4,3	4,6	5,0
3 Syst.	2,0	2,5	3,0	3,5	3,8	4,1
4 Syst.	1,6	2,0	2,4	2,8	3,0	3,3
5 Syst.	1,2	1,5	1,8	2,1	2,3	2,5

Red discharge

Diameter	10	12	15	18	20	22
1 Syst.	1,5	1,8	2,2	2,7	2,9	3,0
2 Syst.	1,2	1,5	1,8	2,2	2,4	2,5
3 Syst.	0,9	1,1	1,4	1,7	1,8	2,0
4 Syst.	0,7	0,8	1,0	1,2	1,3	1,4
5 Syst.	0,4	0,5	0,6	0,8	0,8	0,9

2,000 Volt

Blue discharge (outdoor)

Diameter	10	12	15	18	20	22
1 Syst.	3,0	3,7	4,5	5,3	5,7	6,2
2 Syst.	2,6	3,2	3,9	4,6	5,0	5,4
3 Syst.	2,1	2,7	3,3	3,9	4,2	4,5
4 Syst.	1,7	2,2	2,7	3,1	3,4	3,7
5 Syst.	1,3	1,6	2,2	2,4	2,6	2,8

Blue discharge (indoor)

Diameter	10	12	15	18	20	22
1 Syst.	3,6	4,5	5,4	6,4	6,9	7,5
2 Syst.	3,2	4,0	4,8	5,7	6,1	6,6
3 Syst.	2,8	3,5	4,2	5,0	5,3	5,8
4 Syst.	2,4	3,0	3,6	4,2	4,6	5,0
5 Syst.	2,0	2,5	3,0	3,7	3,8	4,1

Red discharge

Diameter	10	12	15	18	20	22
1 Syst.	1,9	2,3	2,9	3,5	3,7	4,0
2 Syst.	1,6	2,0	2,5	3,0	3,2	3,4
3 Syst.	1,4	1,7	2,1	2,5	2,7	2,9
4 Syst.	1,1	1,3	1,7	2,0	2,2	2,3
5 Syst.	0,8	1,0	1,3	1,6	1,7	1,8

2,500 Volt

Blue discharge (outdoor)

Diameter	10	12	15	18	20	22
2 Syst.	3,2	4,0	5,0	5,8	6,3	6,8
3 Syst.	2,8	3,5	4,3	5,1	5,5	6,0
4 Syst.	2,4	3,0	3,7	4,3	4,7	5,1
5 Syst.	2,0	2,5	3,1	3,6	3,9	4,2
6 Syst.	1,6	2,0	2,5	2,9	3,1	3,4

Blue discharge (indoor)

Diameter	10	12	15	18	20	22
2 Syst.	4,0	5,0	6,0	7,1	7,6	8,3
3 Syst.	3,6	4,5	5,4	6,4	6,9	7,5
4 Syst.	3,2	4,0	4,8	5,7	6,1	6,6
5 Syst.	2,8	3,5	4,2	5,0	5,3	5,8
6 Syst.	2,4	3,0	3,6	4,2	4,6	5,0

Red discharge

Diameter	10	12	15	18	20	22
2 Syst.	2,1	2,5	3,2	3,8	4,1	4,3
3 Syst.	1,8	2,2	2,8	3,3	3,6	3,8
4 Syst.	1,5	1,9	2,4	2,8	3,1	3,2
5 Syst.	1,3	1,6	2,0	2,4	2,5	2,7
6 Syst.	1,0	1,2	1,6	1,9	2,0	2,1

3,000 Volt

Blue discharge (indoor)

Diameter	8	10	12	15	18	20
2 Syst.	4,3	5,6	7,0	8,5	10,0	10,7
3 Syst.	4,0	5,2	6,5	7,9	9,2	10,0
4 Syst.	3,7	4,8	6,0	7,3	8,5	9,2
5 Syst.	3,4	4,4	5,5	6,7	7,8	8,4
6 Syst.	3,1	4,0	5,0	6,0	7,1	7,6

Blue discharge (outdoor)

Diameter	8	10	12	15	18	20
2 Syst.	3,1	4,6	5,7	7,0	8,2	8,9
3 Syst.	2,8	4,2	5,2	6,4	7,5	8,1
4 Syst.	2,5	3,8	4,7	5,8	6,8	7,3
5 Syst.	2,2	3,4	4,2	5,2	6,0	6,5
6 Syst.	1,9	2,8	3,5	4,3	5,1	5,5

Red discharge

Diameter	8	10	12	15	18	20
2 Syst.	2,4	2,9	3,6	4,5	5,4	5,8
3 Syst.	2,2	2,7	3,3	4,1	4,9	5,3
4 Syst.	2,0	2,4	3,0	3,7	4,4	4,8
5 Syst.	1,7	2,1	2,6	3,3	4,0	4,3
6 Syst.	1,5	1,9	2,3	2,9	3,5	3,7

4,000 Volt

Blue discharge (indoor)

Diameter	8	10	12	15	18	20
2 Syst.	5,6	7,2	9,0	10,9	12,8	13,8
3 Syst.	5,3	6,8	8,5	10,3	12,1	13,0
4 Syst.	5,0	6,4	8,0	9,7	11,4	12,3
5 Syst.	4,6	6,0	7,5	9,1	10,7	11,5
6 Syst.	4,3	5,6	7,0	8,5	10,0	10,8
7 Syst.	4,0	5,2	6,5	7,9	9,2	10,0
8 Syst.	3,7	4,8	6,0	7,3	8,5	9,2
9 Syst.	3,4	4,4	5,5	6,7	7,8	8,4

Red discharge

Diameter	8	10	12	15	18	20
2 Syst.	3,1	3,8	4,7	5,8	7,0	7,5
3 Syst.	2,9	3,5	4,4	5,4	6,5	7,0
4 Syst.	2,7	3,3	4,0	5,0	6,0	6,5
5 Syst.	2,5	3,0	3,7	4,6	5,6	6,0
6 Syst.	2,2	2,8	3,4	4,2	5,1	5,5
7 Syst.	2,0	2,5	3,1	3,8	4,6	5,0
8 Syst.	1,8	2,2	2,7	3,4	4,1	4,4
9 Syst.	1,6	2,0	2,4	3,0	3,6	3,9

5,000 Volt

Blue discharge (indoor)

Diameter	8	10	12	15	18	20
2 Syst.	9,3	12,0	15,0	18,2	21,4	23,0
3 Syst.	9,0	11,6	14,5	17,6	20,7	22,3
4 Syst.	8,7	11,2	14,0	17,0	20,0	21,5
5 Syst.	8,4	10,8	13,5	16,4	19,2	20,7
6 Syst.	8,1	10,4	13,0	15,8	18,5	20,0
7 Syst.	7,8	10,0	12,5	15,2	17,8	19,2
8 Syst.	7,5	9,6	12,0	14,6	17,1	18,4
9 Syst.	7,1	9,2	11,5	14,0	16,4	17,6

Red discharge

Diameter	8	10	12	15	18	20
2 Syst.	5,2	6,4	7,9	9,8	11,8	12,7
3 Syst.	5,0	6,2	7,6	9,4	11,3	12,2
4 Syst.	4,8	5,9	7,3	9,0	10,8	11,7
5 Syst.	4,6	5,7	6,9	8,6	10,4	1,2
6 Syst.	4,4	5,4	6,6	8,2	9,9	10,6
7 Syst.	4,2	5,1	6,3	7,8	9,4	10,1
8 Syst.	4,0	4,9	6,0	7,4	8,9	9,5
9 Syst.	3,7	4,6	5,6	7,0	8,4	9,1

8,000 Volt

Best Supply Ltd.
Unit 1602, 16/F., Kowloon Building, 555 Nathan Road,
Yau Ma Tei, Kowloon, Hong Kong
Tel: (852) 25200086 Fax: (852) 25200071

比诚广告器材有限公司
中国办事处: 上海浦东新区樱花路801弄23号102室
邮编: 201204
电话: 021-50596271 传真: 021-50596272
网址: www.bestsupply.com.hk
电邮: china1@bestsupply.com.hk