

## SPECIFICATIONS 产品规格

(*) 230 V 50Hz				LEXABOX / LEXTERIOR		METALBOX	
Type 型号	Sec. Voltage V 次级电压	Case Code 外壳编号	Case Code 外壳编号	Current 电流	Power W 功率	Current A (*) 电流	Power W 功率
				30 mA		30 mA	
990 V	0495-E-0495	1B	1B	0.19	26		
2000 V	1100-E-1100	1B	1B	0.33	40	0.33	40
2500 V	1300-E-1300	1B	1B	0.40	50	0.40	50
3000 V	1500-E-1500	1B	1B	0.48	56	0.48	56
4000 V	2000-E-2000	1B	1B	0.58	70	0.58	70
5000 V	2500-E-2500	1M	1M	0.73	85	0.73	85
6000 V	3000-E-3000	1M	1M	0.86	95	0.86	95
7500 V	3750-E-3750	1A	1A	1.00	120	1.00	120
9000 V	4500-E-4500	1A				1.15	140
10000 V	5000-E-5000	1.5B				1.35	160
12000 V	6000-E-6000	1.5M				1.60	200
15000 V	7500-E-7500	2M				1.90	230
				60 mA		60 mA	
990 V	0495-E-0495	1B	1B	0.34	40		
2000 V	1100-E-1100	1B	1B	0.57	70	0.57	70
2500 V	1300-E-1300	1B	1B	0.71	80	0.71	80
3000 V	1500-E-1500	1M	1M	0.84	98	0.84	98
4000 V	2000-E-2000	1A	1A	1.10	120	1.10	120
5000 V	2500-E-2500	1A	1A	1.26	140	1.26	140
6000 V	3000-E-3000	2B	1.5A	1.57	180	1.57	180
7500 V	3750-E-3750	2B	1.5B	1.80	215	1.80	215
9000 V	4500-E-4500	2M				2.20	250
10000 V	5000-E-5000	2M				2.50	280
12000 V	6000-E-6000	2A				2.90	360
15000 V	7500-E-7500	2A				3.80	480
				90 mA		90 mA	
990 V		1B				0.44	53
2000 V	1000-E-1000		1M			0.83	100
3000 V	1500-E-1500	1A	1A			1.15	140
4000 V	2000-E-2000	2B	2B			1.50	180
5000 V	2500-E-2500	2M	2M			1.90	220
6000 V	3000-E-3000	2M	2M			2.30	260
7000 V	3500-E-3500	2A	2A			2.50	290
8000 V	400 -E-4000	2A	2A			2.80	320
9000 V	4500-E-4500	2S	2S			3.20	370
10000 V	5000-E-5000	2S	2S			3.60	415
				120 mA		120 mA	
990 V		1B				0.59	70
2000 V	1000-E-1000	1A	1A			1.10	120
03000 V	1500-E-1500	2B	2B			1.57	170
04000 V	2000-E-2000	2M	2M			2.05	225
05000 V	2500-E-2500	2M	2M			2.43	270
06000 V	3000-E-3000	2A	2A			2.90	320
07000 V	3500-E-3500	2A	2A			3.39	365
08000 V	4000-E-4000	2S	2S			3.80	420
09000 V	4500-E-4500	2S	2S			4.15	465
10000 V	5000-E-5000	2SM	2SM			4.70	510
				200 mA		200 mA	
1400 V	750-E-750	1A				1.40	125
2100 V	1050-E-1050	1.5A				2.00	175
2800 V	1400-E-1400	2M				2.50	230
3500 V	1750-E-1750	2A				3.10	280
4200 V	2100-E-2100	2A				3.60	330
LEXTERIOR							
				100 mA			
990 V	750-E-750	1B		0.59	70		
1500 V	750-E-750	1M		0.80	95		
2000 V	1000-E-1000	1A		1.10	120		
2500 V	1250-E-1250	1A		1.29	140		
3000 V	1500-E-1500	1.5A		1.80	195		
3500 V	1750-E-1750	1.5A		2.05	225		
				200 mA			
990 V	750-E-750	1A		1.10	120		
COLD CATHODE BALLAST							
				50 mA			
990 V (SINGLE)	990	1B		0.34	40		
2*990 V (TWIN)	990-990	1B		0.57	70		
				100 mA			
990 V (SINGLE)	990	1M		0.59	70		
2*990 V (TWIN)	990-990	1A		1.10	120		
				200 mA			
990 V (SINGLE)	990	1A		1.10	120		
2*990 V (TWIN)	990-990	1.5A		2.00	178		