

## NEON CONVERTORS TECHNICAL SPECIFICATIONS - EN 61347-2-10

Spina (più modelli) e interruttore, su richiesta - Plugs (more types) and in line rocker switches, upon request - Prises (plus models) et interruptor sur le cable, sur demande  
Stecker (bei vielen Modellen) und Trennschalter, auf Anfrage - Enchufes (diversos modelos) e interruptores a pedido - Plugues (mais modelos) e interruptores, sob pedido

TYPE	POWER W	PROT. DEGREE	CASE CODE	INPUT CABLE m	OUTPUT CABLE m	COLOR	DIMMER	FLASH
<b>25 mA</b>								
2525	15	IP 65	1	1,5	0,8 TYPE K	Black/White	NO	NO
5025	30	IP 65	2	1,5	0,8 TYPE K	Black/White	NO	YES
9025	85	IP 40	3	1,5	1,2 TYPE H	Black/White	With Trimmer	YES
<b>50 mA</b>								
2050	30	IP 65	2	1,5	0,8 TYPE K	Black/White	NO	YES
4550	85	IP 40	3	1,5	1,2 TYPE H	Black/White	With Trimmer	YES
6550	135	IP 40	4	1,5	1,2 TYPE H	Black/White	3 steps/0-10V	YES
<b>100 mA</b>								
2010	85	IP 40	3	1,5	1,2 TYPE H	Black/White	With Trimmer	YES
3010	135	IP 40	4	1,5	1,2 TYPE H	Black/White	3 steps/0-10V	YES
4010	165	IP 40	5	1,5	0,5-1,5 max	Light Grey	0-10V	YES
<b>SLIM</b>								
2120	125	IP 40	5	1,5	0,5 - 1,5 max	Light Grey	0-10V	NO
2820	135	IP 40	5	1,5	0,5 - 1,5 max	Light Grey	0-10V	NO
<b>MINI BLAU</b>								
990/20	10	IP 65	1	1,5	0,8 TYPE K	White	NO	YES
990/40	15	IP 65	1	1,5	0,8 TYPE K	White	NO	YES
990/60	20	IP 65	2	1,5	0,8 TYPE K	White	NO	YES
990/80	24,9	IP 65	2	1,5	0,8 TYPE K	White	NO	YES
990/250	103	IP 40	5	1,5	0,5 - 1,5 max	Light Grey	0-10V	NO
500/500	115	IP 40	5	1,5	0,5 - 1,5 max	Light Grey	0-10V	NO
<b>TWIN BLAU</b>								
2x990/20	20	IP 65	6	1,5	0,8 TYPE K	White	NO	NO
2x990/40	30	IP 65	6	1,5	0,8 TYPE K	White	NO	NO
<b>30 mA</b>								
3030	15	IP 65	1	1,5	0,8 TYPE K	Black/White	NO	NO
6030	30	IP 65	2	1,5	0,8 TYPE K	Black/White	NO	YES
11030	85	IP 40	3	1,5	1,2 TYPE H	Black/White	With Trimmer	YES
<b>60 mA</b>								
2060	30	IP 65	2	1,5	0,8 TYPE K	Black/White	NO	YES
5060	85	IP 40	3	1,5	1,2 TYPE H	Black/White	With Trimmer	YES
7560	135	IP 40	4	1,5	1,2 TYPE H	Black/White	3 steps/0-10V	YES

Ingresso - Supply - Anschluss - Entrée - Entrada  
Temperatura - Temperature - Temperatur

220-240V - 50/60Hz  
-10+40°C

### UL

<b>30 mA</b>								
5030	38,5	INDOOR	PICCOLO - 2	1,8 SJT	GTO 5 kV	Black	NO	NO
11030	85	INDOOR	BELLO - 3	1,8 SJT	GTO 10 kV	Black	With Trimmer	NO

Rating 120V - 60 Hz UL Listed models E193557

### INVERTORS

<b>20 mA</b>								
3020	25	INDOOR	2	0,35 + fuse	0,8 TYPE K	Black	NO	NO
4020	32	INDOOR	2	0,35 + fuse	0,8 TYPE K	Black	NO	NO

### CASE CODE

					
1	2	3	4	5	6
Dim. mm. 106x33x32(h)	Dim. mm. 114x44x35(h)	Dim. mm. 202x66x45(h)	Dim. mm. 222x58x47(h)	Dim. mm. 267x77x56(h)	Dim. mm. 162x44x28(h)
Weight kg 0,30	Weight kg 0,40	Weight kg 0,90	Weight kg 1,00	Weight kg 1,50	Weight kg 0,60
					
15	15	10	10	6	10